



LENS SPECIFICATIONS - NMV6WA		
Specification	Value	1/3"
Focal length	f=12.0 mm+/-5%	
Max. Diameter (Ratio)	F=1:1.4+/-5%	
Element	5 Group 6 Elements	
Picture Size	4.8 x 6.4mm	3.6 x 4.8
Angle - Horizontal	23.0	17.2
Vertical	30.7	23.0
Diagonal	38.5	28.8
Distortion (TV)	-0.8%	
Shooting Range @ M.O.D. - Horizontal	123 mm	
Verical	167 mm	
Diagonal	213 mm	
Minimum Object Distance	0.3m	
Flange Back	17.526 mm in air	
Back Focus	11.12 mm in air	
Filter Screw Size	M30.5 x 0.5	
Effective Diameter - Front -	12.3 mm dia.	
Rear -	11.7 mm dia.	
Mount	C - Mount	
Exit Pupil	-38.9 mm	
Temperature Range	-10 ~ +45 deg. C	
Strong Temperature Range	-40 ~ +60 deg. C	
Resolution - Center -	100 Line/mm	
Cornter	40 Line/mm	
Stopper Strength	10 kgf * cm	
Endurance Tests - Iris -	5000 Times	
Focus -	5000 Times	
Operating Torque - Iris -	50 ~ 600 gf * cm	
Focus -	100 ~ 1000 gf * cm	
Weight -	60g+/-5g	



OUTLINE

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND INCLUDE CHEMICALLY APPLIED OR PLATED FINISHES	
SCALE:	1:1
WEIGHT:	See Table
DR:	BE
CH:	
PROJECT #:	E2338
DATE DR:	7/10/2007

THE CONTENTS OF THIS DOCUMENT ARE PROPRIETARY TO NAVITAR. ITS USE IS AUTHORIZED ONLY FOR RESPONDING TO REQUEST FOR QUOTATION OR PERFORMANCE OF WORK FOR NAVITAR	
0.0	1.0
inch	
0.0	25.0
mm	
DO NOT SCALE DRAWING	

 ROCHESTER, NEW YORK	
LENS, 12.0 mm FL, WD. ANG., 1/2", f/1.4	
SIZE	REV
A	A
NMV -12WA SHEET 1 OF 1	